

SPOT STREAMER RETARDING AIR TERMINAL STAINLESS STEEL



APPLICATION:

UL listed air terminal (lightning rod) suitable for use in any NFPA 780 or UL 96A system where streamer delaying or static dissipating qualities are desired. These are blunt lightning rods with streamer delaying electrodes. Electrodes are available in stainless steel, Hastelloy®, or titanium.

AVAILABLE:

- DAT-118SS 5/8" X 18" solid stainless steel air terminal 1/2"thread, 1/2" lock washer & jam nut
- DAT-124SS 5/8" X 24" solid stainless steel air terminal 1/2"thread, 1/2" lock washer & jam nut
- DAT-136SS 5/8" X 36" solid stainless steel air terminal 1/2"thread, 1/2" lock washer & jam nut
- DAT-148SS 5/8" X 48" solid stainless steel air terminal 1/2"thread, 1/2" lock washer & jam nut
- DAT-160SS 5/8" X 60" solid stainless steel air terminal 1/2"thread, 1/2" lock washer & jam nut

LBA Group Inc. is an authorized dealer of

LightningMaster
Corporation



©2024 Lightning Master Corporation

This data sheet is confidential, and all rights are reserved. It shall not be reproduced, or copied, for any other purpose than for which it is specifically furnished.