

## SPOT STREAMER RETARDING AIR TERMINAL ALUMINUM



### APPLICATION:

UL listed air terminal (lightning rod) suitable for use in any NFPA 780 or UL 96A system where streamer delaying or static dissipating qualities are desired. These are blunt lightning rods with streamer delaying electrodes. Electrodes are available in stainless steel, Hastelloy<sup>®</sup>, or titanium.

### AVAILABLE:

DAT-112A 1/2" X 12" aluminum air terminal with 1/2" thread, 1/2" lock washer and jam nut.

DAT-118A 1/2" X 18" aluminum air terminal with 1/2" thread, 1/2" lock washer and jam nut.

DAT-124A 1/2" X 24" aluminum air terminal with 1/2" thread, 1/2" lock washer and jam nut.

DAT-136A 1/2" X 36" aluminum air terminal with 1/2" thread, 1/2" lock washer and jam nut.

DAT-148A 1/2" X 48" aluminum air terminal with 1/2" thread, 1/2" lock washer and jam nut.

DAT-160A 1/2" X 60" aluminum air terminal with 1/2" thread, 1/2" lock washer and jam nut.

LBA Group Inc. is an authorized dealer of

**LightningMaster**  
Corporation



©2024 Lightning Master Corporation

This data sheet is confidential, and all rights are reserved. It shall not be reproduced, or copied, for any other purpose than for which it is specifically furnished.