

## UL LISTED OFFSET ULTRA-SHARP POINT AIR TERMINAL - ALUMINUM DAT-1xxAO



### APPLICATION:

UL listed air terminal (lightning rod) suitable for use in NFPA 780 or UL 96A systems where streamer-delaying or static-dissipating qualities are desired. Ideal for use wherever an offset is required. These terminals are designed with ultra-sharp point electrodes for efficient lightning protection.

### INSTALLATION:

Ensure compliance with UL 96A and NFPA 780 standards during installation. The air terminal is mounted on a base suitable for the structure. Mounting hardware and base compatibility should be verified with the LBA Group expert.

### AVAILABLE:

**DAT-136AO** 5/8" x 36" aluminum with 6" offset, 1/2" thread, 1/2" lock washer, and jam nut

**DAT-148AO** 5/8" x 48" aluminum with 6" offset, 1/2" thread, 1/2" lock washer, and jam nut

**DAT-160AO** 5/8" x 60" aluminum with 6" offset, 1/2" thread, 1/2" lock washer, and jam nut

Custom sizes available upon request.

LBA Group Inc. is an authorized dealer of

**LightningMaster**  
Corporation



©2025 Lightning Master Corporation

This data sheet is confidential, and all rights are reserved. It shall not be reproduced, or copied, for any other purpose than for which it is specifically furnished.

Rev.2.25