LBA TECHNOLOGY

UNIVERSAL CABLE SPLICE



APPLICATION:

UL listed universal cable splice featuring an innovative pressed bolt design that ensures a smooth, flat surface. Ideal for use on membrane roofs without causing damage and provides greater ease of installation.

AVAILABLE:

CN-SPLICE-A - 2" square aluminum bolt cross run splicer with 1-1/2" conductor contact. Accepts conductors and rods up to 5/8" diameter and grounding conductors from #6 AWG to 250 MCM.

CN-SPLICE-C - 2" square copper bolt cross run splicer with 1-1/2" conductor contact. Accepts conductors and rods up to 5/8" diameter and grounding conductors from #6 AWG to 250 MCM.

CN-SPLICE-TC - 2" square tinned copper bolt cross run splicer with 1-1/2" conductor contact. Accepts conductors and rods up to 5/8" diameter and grounding conductors from #6 AWG to 250 MCM.

CN-SPLICE-SS-L - 2" square stainless steel parallel cable splicer, bimetallic rated, with 1-1/2" cable contact for full-size conductors or secondary bonding wire.

LBA Group Inc. is an authorized dealer of LightningMaster Corporation

©2024 Lightning Master Corporation

This data sheet is confidential, and all rights are reserved. It shall not be reproduced, or copied, for any other purpose than for which it is specifically furnished

An LBAGROUP® Company

3400 Tupper Drive, Greenville, North Carolina 27834

Phone: 800-522-4464 / 252-757-0279 | Fax 252-752-9155 | Email: lbagrp@lbagroup.com | www.lbagroup.com